Zero-Liquid Discharge Desalination of Hypersaline Shale Gas Wastewater: Challenges and Future Directions

Viviani C. Onishi, Juan A. Reyes-Labarta, José A. Caballero
Institute of Chemical Process Engineering, University of Alicante
viviani.onishi@ua.es

Introduction

Unconventional natural gas extraction from tight shale reservoirs, or “shale gas”, has recently emerged as an attractive energy resource to face the rising worldwide demand. Over the past decade, advanced technologies of horizontal drilling and hydraulic fracturing (“fracking”) have allowed the economic viability of shale gas exploration from previously unattainable deposits. Despite optimistic growth projections from the U.S. Energy Information Administration [1,2], shale gas production is also responsible for worrying environmental and social implications, which are related, among others, to elevated freshwater consumption and hazardous wastewater generation [3].

Within this framework, the application of effective desalination processes is mandatory to treat the large amounts of polluting hypersaline wastewater, alleviating environmental and public health impacts and enhancing overall sustainability of shale gas process [4,5]. Hence, the ability of zero-liquid discharge (ZLD) desalination to promote water reuse and/or water recycling (i.e., water reuse opportunities aside from shale gas operations) could be critical for further development of the shale gas industry. This work outlines the main challenges and future directions for the wide implementation of ZLD desalination processes for shale gas wastewater.

Figure 1. Management alternatives for the wastewater from shale gas industry

ZLD Desalination for Wastewater Management: Emerging Zero-Emission Technologies

ZLD desalination, as a strategy for shale gas wastewater management, has received increased interest in the past few years. This is mainly due to its capability to comply with the severe regulations on water quality—especially for allowing water recycling or safe disposal—by enhancing freshwater recovery efficiency, while reducing brine discharges [6]. Emerging technologies for the ZLD desalination of shale gas wastewater comprise thermal and membrane-based processes. Thermal-based desalination alternatives include multistage flash distillation (MSF), and single/multiple-effect evaporation systems combined with mechanical/thermal vapor compression (SEE/MEE-MVC/TV) [7]. On the other hand, membrane distillation (MD), forward osmosis (FO), reverse osmosis (RO), and nanofiltration (NF), and electrodialysis (ED), are promising membrane-based processes. Evidently, the selection of the most appropriate desalination alternative is greatly dependent on the wastewater physicochemical composition [8].

Apart from the possibility to be operated with low-grade energy sources, membrane-based schemes generally present high water recovery efficiencies, simple scale-up and modular features, and elevated permeability and selectivity for critical components [9]. However, thermal evaporation systems can be more advantageous than membrane ones for the zero-emission treatment of shale gas wastewater, as a result of their need for less intensive pretreatment and lower susceptibility to fouling and rusting problems that can be caused by the presence of greases, oil and scale-forming ions [10].

Figure 2. Schematic representation of major thermal and membrane-based processes for shale gas wastewater desalination

Figure 3. Conceptual profiles for TDS concentrations and wastewater flowrates in function of the time following the horizontal drilling and hydraulic fracturing operations

Figure 4. Schematic representation of a thermal-based ZLD evaporation plant coupled to the pretreatment system and crystallization or evaporation ponds

Challenges of ZLD Desalination of Hypersaline Shale Gas Wastewater

Shale gas wastewater generated by hydraulically-fractured wells can present chemical and physical properties varying according to different factors, which include geographic location and formation geology, hydrofracturing fluid composition, as well as its time of contact with shale deposits [8,10]. Also, the concentration of chemicals in shale gas wastewater may change over the time of well exploration [10]. In addition to the chemical additives used within fracking fluids, shale gas wastewater generally contains formation-based constituents, comprising salt and other minerals—such as the scale-forming divalent ions: Ca, Ba and Mg —, organic matter and naturally occurring radioactive materials (NORM) [11,12].

Among them, removal of the elevated salt contents from shale gas wastewater (average values >100k ppm TDS – Total Dissolved Solids) is notably challenging because of the energy-intensive consumption required to achieve the ZLD brine conditions. In Onishi et al. [5], thermal technologies for ZLD desalination (brine discharge at 300 g kg⁻¹) have presented energy consumption in a range of 28.12–50.47 kWh m⁻³, with specific operational costs estimated between 2.73–4.90 US\$ m⁻³ for 77% conversion ratio. Furthermore, another complicating factor is related to the significant composition variations observed in wastewater from different shale basins, and even in distinct wellbores from the same well pad [13].

The elevated consumption of high-grade electrical energy is also responsible for significant greenhouse gas (GHG) emissions. Besides the prohibitive costs related to the raised energy consumption, high salt concentrations in the shale gas wastewater pose particular desalination challenges, mostly associated with operational problems caused by fouling, scaling and corrosion [14]. Due to changes in process temperature conditions, fouling and scaling can reduce heat transfer in thermal systems and mass transfer rate in membrane-based technologies. Lastly, appropriate management of the generated solid brine should be considered to avoid potential environmental impacts.

Outlook and Future Directions

The main advantages of ZLD systems include their ability to achieve high water efficiencies and comply with tight water quality regulations, allowing almost the totality of water contents in wastewater to be reclaimed for reuse or even recycling opportunities.

Despite of the increasing worldwide interest on the implementation of ZLD desalination systems, their intensive energy consumption and high related operating costs remain as obstacles for their further adoption. Future advances on ZLD applications will ultimately be achieved by the development of more energy efficient and sustainable thermal-based desalination processes. Also, technological advances in fouling control, membranes materials and draw solutions, together with operating conditions optimization, should further increase economic and energy efficiency affordability of membrane ZLD desalination systems within shale gas activity.

Eventually, stricter regulations on wastewater disposal and water quality, along with the raise in wastewater disposal costs and regulatory incentives for financial counterweighting, should drive shale gas industry towards the adoption of cleaner ZLD desalination systems.

References

- [1] EIA. Annual Energy Outlook 2016 with Projections to 2040. Washington, DC: U.S. Energy Information Administration, 2016.
- [2] EIA. International Energy Outlook 2016. Washington, DC: U.S. Energy Information Administration, 2016.
- [3] Thomas M, Partridge T, Harthorn BH, Pidgeon N. Deliberating the perceived risks, benefits, and societal implications of shale gas and oil extraction by hydraulic fracturing in the US and UK. *Nat Energy* 2017;2:17054.
- [4] Onishi VC, Carrero-Parreño A, Reyes-Labarta JA, Fraga ES, Caballero JA. Desalination of shale gas produced water: A rigorous design approach for zero-liquid discharge evaporation systems. *J Clean Prod* 2017;140:1399–414.
- [5] Onishi VC, Carrero-Parreño A, Reyes-Labarta JA, Ruiz-Femenia R, Salcedo-Díaz R, Fraga ES, et al. Shale gas flowback water desalination: Single vs multiple-effect evaporation with vapor compression cycle and thermal integration. *Desalination* 2017;404:230–48.
- [6] Tong T, Elmehrik M. The Global Rise of Zero Liquid Discharge for Wastewater Management: Drivers, Technologies, and Future Directions. *Environ Sci Technol* 2016;50:6846–55.
- [7] Onishi VC, Ruiz-Femenia R, Salcedo-Díaz R, Carrero-Parreño A, Reyes-Labarta JA, Fraga ES, et al. Process optimization for zero-liquid discharge desalination of shale gas flowback water under uncertainty. *J Clean Prod* 2017;164:1219–38.
- [8] Lester V, Ferrer I, Thurman EM, Sitterley KA, Korak JA, Alken G, et al. Characterization of hydraulic fracturing flowback water in Colorado: Implications for water treatment. *Sci Total Environ* 2015;512–513:637–44.
- [9] Drioli E, Ali A, Lee YM, Al-Sharif SF, Al-Beiruty M, Macedonio F. Membrane operations for produced water treatment. *Desalin Water Treat* 2016;57:14317–35.
- [10] Shaffer DL, Arias Chavez LH, Ben-Sasson M, Romero-Vargas Castrillón S, Yip NY, Elmehrik M. Desalination and Reuse of High-Salinity Shale Gas Produced Water: Drivers, Technologies, and Future Directions. *Environ Sci Technol* 2013;47:9568–83.
- [11] Zhang Y, Gregory K, Hammack RW, Vidic RD. Co-precipitation of Radium with Barium and Strontium Sulfate and Its Impact on the Fate of Radium during Treatment of Produced Water from Unconventional Gas Extraction. *Environ Sci Technol* 2014;48:4596–603.
- [12] Rahm BG, Riha SI. Toward strategic management of shale gas development: Regional, collective impacts on water resources. *Environ Sci Policy* 2012;12:2–23.
- [13] Thiel GP, Lienhard JH. Treating produced water from hydraulic fracturing: Composition effects on scale formation and desalination system selection. *Desalination* 2014;346:54–69.
- [14] Kaplan R, Mamosh D, Salih HH, Dastgheib SA. Assessment of desalination technologies for treatment of a highly saline brine from a potential CO2 storage site. *Desalination* 2017;404:87–101.

Acknowledgement

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 640979